

A432

Specially designed to be as lightweight as possible, the Phoenix harness is recommended for your compliance, restraint and fall arrest applications.

For further information, refer to "Use and Maintenance Instructions" for harnesses, belts and lanyards.

Features

- Adjustable back D-ring
- Adjustable chest strap
- Sewn sub-pelvic strap
- Three-point adjustment
- Inspection tag / serial number
- Blue color

Sizes

- One size: A432 (fits most)
- Small: A432S
- X-large: A432XL


Applications

- Restraint
- Fall arrest
- Optional work positioning

Applicable standards

- ANSI Z359.1-2007 and A10.32-2004
- OSHA 1926

AVAILABLE MODELS




Quick connect legs

A432 – Quick connect legs



- Fall arrest attachment element (mandatory)
- Fall arrest applications




Side positioning D-rings

A442 – Quick connect legs



- Side positioning D-rings
- Fall arrest and work positioning applications

MODULAR CAPABILITY



Belt loops

The Phoenix harness has belt loops to accommodate any Tractel® belts or your favorite tool belt which is up to 4 in. (102 mm) wide.

PARTS	SPECIFICATIONS	APPLICABLE STANDARDS
Webbing	High tenacity polyester Width: 1¾ in. (45 mm) Thickness: ¼ in. (1.4 mm) Tensile strength: 5,700 lbs. (25.4 kN) Webbing is heat-cut to prevent fraying.	ANSI Z359.1-2007 CSA Z259.10-06
Stitching	Harness is lock-stitched. Thread: #138 polyester	CSA Z259.10-06
Back and side D-ring	Plating: zinc dichromate Proof-loaded 100% at 3,600 lbs. (16 kN) Tensile strength: 5,000 lbs. (22.2 kN)	ANSI Z359.1-2007 CSA Z259.12-01
Quick connect buckle	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	ANSI Z359.1-2007 CSA Z259.12-01
Tongue and buckle	Plating: zinc dichromate Tensile strength: 4,000 lbs. (17.8 kN)	ANSI Z359.1-2007 CSA Z259.12-01
Grommets	#2 spur brass	
Elastic retainers	Each webbing strap with a free end has keeper loops.	CSA Z259.10-06
Capacity	310 lbs. (140 kg), one person	ANSI Z359.1-2007